



Mobil Delvac Legend™ 15W-40 Protection

Mobil Commercial Vehicle Lube , Argentina

High Performance Diesel Engine Oil

Product Description

Mobil Delvac Legend™ 15W-40 Protection is a high-performance lubricant specially designed for use in four-stroke high-speed diesel engines that meet emission control standards. This product is formulated to maintain the durability of engines equipped with exhausted gas recirculation (EGR) systems and using diesel fuel with a sulfur content of up to 0.5% by weight.

Features and Benefits

Mobil Delvac Legend 15W-40 Protection provides excellent performance in both modern and older diesel engines. Its unique formulation helps control oil consumption and engine durability by reducing metal wear.

Features	Advantages and Potential Benefits
Wear protection of all critical engine components	Longer engine life
Shear stability	Lower oil consumption and wear protection
Excellent detergency/dispersance	Clean motors with a long service life
Thermal stability and oxidation resistance	Control of sludge and deposit accumulation
TBN Reserve	Tank control

Applications

Mobil Delvac Legend 15W-40 Protection can be used in diesel engines installed in heavy-duty vehicles operating in urban and on highway services or construction equipment and transportation materials. This oil can also be used in engines that require compliance with the CI-4 specification and the previous CH-4, CG-4 and CF-4 specifications.

Specifications and Approvals

This product meets or exceeds the requirements of:
API CI-4
API CH-4

Properties and Specifications

Property	
Grade	SAE 15W-40
Total Base Number, mgKOH/g, ASTM D2896	8.3

Property	
Pour Point, °C, ASTM D97	-33
Appearance, AMS 1738	Clear and Bright
Viscosity Index, ASTM D2270	130
Density @ 15.6 C, g/ml, ASTM D4052	0.8762
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.3
Flash Point, Cleveland Open Cup, °C, ASTM D92	236

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2024

Cosan Lubricantes S.R.L.

Av. Libertador 6343, Piso 8

CABA, CP 1498, Buenos Aires – Argentina

0800 345 79540

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved