



Mobil Super™ 2000 X1 10W-40

Mobil Passenger Vehicle Lube , Austria

Premium Semi-Synthetic Passenger Vehicle Motor Oil

Product Description

Mobil Super™ 2000 engine oils are premium engine oils engineered to provide an excellent level of protection.

Mobil Super™ 2000 X1 10W-40 is formulated for city driving conditions in both gasoline and Diesel vehicles. It is suitable for passenger cars, light commercial vehicles, and vans across a wide range of temperatures. This oil provides good wear protection and maintains engine cleanliness, helping to extend the life of your engine.

Features and Benefits

Mobil Super™ 2000 x1 10W-40 provides:

- Effective sludge prevention
- Good engine cleanliness
- Robust wear protection
- High temperature protection

Applications

Mobil Super™ 2000 products are formulated to give you confidence of protection beyond that of conventional oils. Mobil Super 2000™ x1 10W-40 is recommended for:

- Older engine technologies
- Gasoline and Diesel engines without Diesel Particulate Filters (DPF)
- Passenger cars, SUVs, light commercial vehicles, and vans
- Highway cruising and stop-and-go city driving
- Normal to occasionally severe operating conditions

Always consult your owner's manual to check the recommended viscosity grade and specifications for your vehicle.

Specifications and Approvals

This product has the following approvals:
VW 501 01
VW 505 00

This product is recommended for use in applications requiring:
ACEA A3/B3-16
API CF
MB 229.1

This product meets or exceeds the requirements of:
--

This product meets or exceeds the requirements of:

API SN

API SN PLUS

API SP

API SQ

Properties and Specifications

Property	
Grade	SAE 10W-40
Density @ 15.6 C, g/ml, ASTM D4052	0.865
Flash Point, Cleveland Open Cup, °C, ASTM D92	234
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.7
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	102
Viscosity Index, ASTM D2270	150
Pour Point, °C, ASTM D97	-33

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2025

ExxonMobil Lubricants & Specialties Europe, division of ExxonMobil Petroleum & Chemicals BVBA.

This information relates only to products supplied in Europe (including Turkey) and the Former Soviet Union.

EXXONMOBIL LUBRICANTS & SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM & CHEMICAL, BVBA (EMPC)

POLDERDIJKWEG

B-2030 Antwerpen

Belgium

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.




© Copyright 2003-2026 Exxon Mobil Corporation. All

Rights Reserved