



Mobil Delvac Modern™ 1340

Mobil Commercial Vehicle Lube , Bolivia

Product Description

Mobil Delvac Modern™ 1340 is a high performance monograde diesel engine oil formulated from advanced technology base oils and a balanced additive system. It is specifically engineered for performance in intercooled, turbo-charged engines operating under severe on and off-highway conditions. Also used in some commercial vehicles manual transmissions.

Features and Benefits

| Features | Advantages and Potential Benefits |
|------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| Excellent protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion | Prolonged engine life, Less wear, Excellent protection against ring sticking |
| Extended TBN reserve | Long-term deposit/wear control, Controls formation of acids when using higher sulfur fuels |

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment
- On highway light and heavy duty trucking
- Off highway industries including: construction, mining, quarrying, and agriculture
- Applications where API CF or API SF quality level lubricants are required

Specifications and Approvals

| This product is recommended for use in applications requiring: |
|----------------------------------------------------------------|
| API CF |
| API SF |

Properties and Specifications

| Property | |
|------------------------------------------------------------|------------------|
| Grade | SAE 40 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 14.7 |
| Appearance, AMS 1738 | Clear and Bright |

| Property | |
|-----------------------------------------------|-----|
| Pour Point, °C, ASTM D97 | -30 |
| Viscosity Index, ASTM D2270 | 100 |
| Total Base Number, mgKOH/g, ASTM D2896 | 10 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 264 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2024

ExxonMobil

Exxon Mobil Esso XTO ENERGY

© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved