# Mobil Delvac™ MX LD 5W-30

Mobil Commercial Vehicle Lube , Brazil

Synthetic Light Commercial Vehicle Engine Oil

## Product Description

Mobil Delvac™ MX LD 5W-30 is a low ash synthetic engine oil that provides long engine life and excellent engine protection against sludge and wear.

Mobil Delvac™ MX LD 5W-30 provides excellent lubrication of diesel and gasoline engines operating in severe driving conditions typically encountered in city operations.

## Features and Benefits

Mobil Delvac™ MX LD 5W-30 is formulated from high performance base oils and a superior balanced additive system to provide optimum engine performance in recent diesel and gasoline engines as well as older models: It is fully compatible with most Diesel Particulate Filters and Catalytic Convertors. Key benefits include:

| Features | Advantages and Potential Benefits |
|---|---|
| Increased thermal and oxidation stability | Help to reduced sludge build-up, deposits, and long oil and engine life |
| Enhanced wear protection | Helps towards long component and engine life |
| Advanced piston deposit control | Helps to keep engines clean with reduced maintenance costs and long engine life |
| Advanced soot handling to control viscosity increase, sludge build up, and filter pressure | Helps to enhanceengine protection for long engine life |
| Enhanced low temperature pumpability | Fast start up with reduced wear operating in low temperature climates |
| Stayed in viscosity grade | Helps to maintain fuel economy |

## Applications

Mobil Delvac™ MX LD 5W-30 is a low ash synthetic engine oil that provides long engine life and excellent engine protection against sludge and wear.

Mobil Delvac™ MX LD 5W-30 provides excellent lubrication of diesel and gasoline engines operating in severe driving conditions typically encountered in city operations.

## Specifications and Approvals

| This product is recommended for use in applications requiring: |
|---|
| Ford WSS-M2C917-A |

| This product is recommended for use in applications requiring: |
|---|
| API CF |

| This product meets or exceeds the requirements of: |
|---|
| API SM |
| API SN |

## Properties and Specifications

| Property | |
|---|---|
| Grade | SAE 5W-30 |
| Density @ 15 C, kg/l, ASTM D4052 | 0.8516 |
| Pour Point, °C, ASTM D97 | -33 |
| Noack Volatility, mass%, ASTM D5800 | 9 |
| Total Base Number, mgKOH/g, ASTM D2896 | 8 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 234 |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 11.9 |
| Viscosity Index, ASTM D2270 | 170 |

## Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2024
Cosan Lubrificantes e Especialidades S.A.

Praia da Ribeira, 01

21930-080 Rio de Janeiro – RJ - BRASIL
**Tel:** 0800 644 1562

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved