



Mobil ATF™ LT 71141

Mobil Passenger Vehicle Lube , Belarus

Automatic Transmission Fluid

Product Description

Mobil ATF LT71141 is a high performance ATF with long drain-performance to be applied in automatic vehicle gearboxes.

Features and Benefits

Excellent cold properties.

Balanced additive performance ensuring a smooth transmission.

Applications

Mobil ATF LT71141 is designed to meet the specific requirements of automatic transmissions.

Mobil ATF LT71141 is used for the AL4 and 4HP20 gear boxes as the automatic transmission fluid.

Specifications and Approvals

This product has the following approvals:

PSA B71 2340

ZF TE-ML 04D

ZF TE-ML 11B

ZF TE-ML 14B

ZF TE-ML 17C

MB-Approval 236.11

DTFR 13C110

This product is recommended for use in applications requiring:

VW TL 52162

Properties and Specifications

Property	
Density @ 15 C, g/cm3, ASTM D4052	0.855

Property	
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	7.4
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	37.2
Viscosity Index, ASTM D2270	168

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2024

ExxonMobil



© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved