



## Mobil Delvac Legend™ 20W-50 High Mileage

Mobil Commercial Vehicle Lube , Central America

High Performance Diesel Engine Oil

### Product Description

The technology behind Mobil Delvac Legend™ 20W-50 High Mileage provides excellent performance in both modern and older diesel engines.

Mobil Delvac Legend™ 20W-50 High Mileage is recommended by ExxonMobil for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying and agricultural industries.

### Features and Benefits

More than 90 years of experience and innovation supports the technology in Mobil Delvac Legend™ 20W-50 High Mileage. Delivers excellent performance in both naturally aspirated as well as turbo-charged diesel-powered equipment. The key benefits include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
TBN reserve	Deposit control and acid neutralization
High Viscosity and Stay-in-grade shear stability	Reduced oil consumption, increased wear protection and high oil pressure across a wide operating temperature range
Excellent detergency/dispersancy	Cleaner engines and prolonged engine life
Component compatibility	Long gasket and seal life

### Applications

- Naturally aspirated and turbo-charged diesel-powered equipment European, Japanese, and American manufacturers
- On-highway light and heavy-duty trucking
- Off-highway industries including construction, mining, quarrying, and agriculture

### Specifications and Approvals

<b>This product meets or exceeds the requirements of:</b>
API CH-4

### Properties and Specifications

<b>Property</b>	
-----------------	--

Property	
Grade	SAE 20W-50
Pour Point, °C, ASTM D97	-36
Density @ 15.6 C, g/ml, ASTM D4052	0.889
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	18.7

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2023

ExxonMobil de Colombia S.A.

Calle 90 N° 21-32 , Bogota , Colombia

(571) 628 - 0460

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved