Mobil

Mobilgrease™ FM Series

Mobil Grease , 中国

Grease

Product Description

Mobilgrease™ FM 101 and FM 222 are high performance multi-purpose products designed specifically for the lubrication of food processing machinery. Mobilgrease FM 101 and FM 222 are formulated with components meeting the requirements of CFR 178.3570, Chapter 21, and are NSF registered as H1 classified lubricants. Mobilgrease FM 101 and FM 222 are manufactured in ISO 22000 certified facilities and in accordance with the hygiene and manufacturing principles of ISO 21469, supporting controlled production conditions and a high level of product integrity for food industry applications.

Food processing equipment often operates in a variety of environments, covering the extremes of temperatures from oven to freezer operations, as well as a high level of contamination from water, steam and cleaning agents. Mobilgrease FM 101 and FM 222 were developed as multipurpose grease lubricants capable of providing excellent lubrication in all of these environments. Mobilgrease FM 101 and FM 222 are engineered with excellent water resistance to withstand periodic washdown and cleaning operations frequent in the food processing industry. Rust inhibition is a critical property for the industry. Mobilgrease FM 101 and FM 222 are formulated with an excellent rust inhibition package which, working in concert with the water resistance properties, will provide protection against rust. The select base oils coupled with excellent thickener shear stability translates into an ability to provide lubrication over a wide range of speeds, loads and temperatures. Mobilgrease FM 101 and FM 222 are also formulated to handle a variety of loads, exhibiting good protection against wear and shock load conditions.

Mobilgrease FM 101 and FM 222 were designed to meet many global performance and cultural requirements, including:

- NSF H1 Registered
- DIN 51825 KPF1K -20 (for Mobilgrease FM 101)
- DIN 51825 KPF2K-20 (for Mobilgrease FM 222)
- Kosher/Parve
- Halal

This formulation does not intentionally include components containing mineral oil fractions associated with mineral oil aromatic hydrocarbons (MOAHs), reflecting current scientific understanding and industry best practices for lubricants intended for incidental food contact.

Features and Benefits

Mobilgrease FM 101 and FM 222 belong to the Mobilgrease brand of products, which has gained a worldwide reputation for innovation and performance excellence. Mobilgrease FM 101 and FM 222 are designed by ExxonMobil formulation technologists and backed by its worldwide technical support staff.

Mobilgrease FM 101 and FM 222 greases have been designed specifically to meet the needs of the food processing industry that requires excellent water resistance, rust protection and a lubricant able to provide oil to the load zones reliably under high shear conditions. These greases offer the following features and potential benefits:

Features	Advantages and Potential Benefits
Excellent water resistance and rust protection	Helps provide superb equipment protection during frequent equipment cleaning operations
Excellent thickener shear stability	Product exhibits excellent stability for long periods of time, helping to provide oil more consistently between relubrication cycles
NSF H1 registered, DIN51825certified, Kosher/Parve, Halal	Engineered to meet global requirements, presenting a multi-purpose solution to the food processing industry around the world
Manufactured in facilities registered to ISO 21469	Product integrity assurance through independent verification

Applications

Mobilgrease FM 101 and FM 222 greases are recommended for multi-purpose lubrication of food processing equipment where NSF H1 registration is required. The food industry includes food processing, beverage and packing industries for a wide range of cultures.

Applications include:

- General rotating equipment lubrication
- Conveyor bearings
- Equipment central lubrication systems (Mobilgrease FM 101)
- Anti-friction roller bearings under heavy or shock loading

- Linkages and slides
- Joints

Specifications and Approvals

This product has the following builder approvals:	FM 101	FM 222
Halal Halal	X	X
Kosher & Parve Kosher & Parve	X	X

This product is recommended for use in applications requiring:	FM 101	FM 222
Fives Cincinnati P-64		X
Fives Cincinnati P-72	X	

This product is registered to the requirements of:	FM 101	FM 222
This product has met the requirements of the NSF ISO 21469 certification for lubricants with incidental product contact.	X	X
NSF H1	X	X

This product meets or exceeds the requirements of:	FM 101	FM 222
DIN 51825:2004-06 - KPF 1 K -20	X	
DIN 51825:2004-06 - KPF 2 K -20		X
FDA 21 CFR 178.3570	X	X

Properties and Specifications

Property	FM 101	FM 222
Grade	NLGI 1	NLGI 2
Thickener Type	Aluminium Complex Greases	Aluminium Complex Greases
Color, Visual	White	White
Corrosion, Cu 24H at 120C, Rating, DIN 51811	1	1
Dropping Point, °C, ASTM D2265	260	260
FAG FE9, 1500 N, 6000 RPM, Unshielded at 120C, L50 hrs., DIN 51821	120	120
Four-Ball Extreme Pressure Test, Weld Point, kgf, ASTM D2596	315	315
Four-Ball Wear Test, Scar Diameter, mm, ASTM D2266	0.5	0.5
Penetration, 60X, 0.1 mm, ASTM D217	325	280
SKF Emcor Rust Test, Distilled Water, ASTM D6138	0 , 0	0 , 0

Property	FM 101	FM 222
Viscosity @ 40 C, Base Oil, mm2/s, ASTM D445	100	220

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2026
ExxonMobil (China) Investment Co. Ltd
17th Floor, Metro Tower
30 Tian Yao Qiao Road
Shanghai 2000030
China

+86 21 24076000
http://www.exxonmobil.com

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved