



Mobil Super™ 2000 5W-20

Mobil Passenger Vehicle Lube , Colombia

Synthetic Blend Motor Oil

Product Description

Mobil Super™ 2000 5W-20 is formulated from quality base stocks combined with modern performance additives to provide the engine protection and performance you expect under a wide variety of operating conditions. Mobil Super™ 2000 5W-20 come with the Mobil Limited Warranty*. Mobil Super™ 2000 5W-20 meet warranty requirements where an American Petroleum Institute (API) certified oil is specified.

Features and Benefits

Mobil Super™ 2000 5W-20 is formulated from quality base stocks combined with modern performance additives to provide the engine protection and performance you expect under a wide variety of operating conditions.

Key features and potential benefits include:

Features	Advantages and Potential Benefits
Meets or exceeds the latest industry specifications	OEM warranty protection
Modern performance additives	Reduces wear and corrosion
Warranty	Mobil Special Limited Warranty*
Tested, proven engine protection	Protects under a wide variety of operating conditions
Engine cleansing agents	Helps prevent the formation of sludge and deposits

Applications

Mobil Super™ 2000 5W-20 is recommended by ExxonMobil for all types of modern gasoline-powered engines found in passenger cars, SUVs, light vans and light trucks.

- Mobil Super™ 2000 5W-20 meet warranty requirements where an American Petroleum Institute (API) certified oil is specified.
- Mobil Super™ 2000 5W-20 is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

Always check your owner's manual for the manufacturer's recommended oil viscosity grade, API service classification and any builder approval

Specifications and Approvals

This product is recommended for use in applications requiring:
Ford WSS-M2C930-A
GM 6094M

This product meets or exceeds the requirements of:
API SJ
API SL
API SM

This product meets or exceeds the requirements of:
API SN
API SN PLUS
API SN PLUS RESOURCE CONSERVING
API SN Resource Conserving
API SP
API SP Resource Conserving
API SQ
API SQ Resource Conserving
ILSAC GF-6A
ILSAC GF-7A
Ford WSS-M2C945-A
Ford WSS-M2C945-B1
FORD WSS-M2C960-A1

Properties and Specifications

Property	
Grade	SAE 5W-20
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	48.8
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	8.3
Density @ 15.6 C, g/ml, ASTM D4052	0.86
Viscosity Index, ASTM D2270	146
Pour Point, °C, ASTM D97	-42
Flash Point, Cleveland Open Cup, °C, ASTM D92	216

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2026

Organización Terpel S.A.

Address: Carrera 7 N° 75-51, Bogotá – Colombia

Phone: (57) 1 3267878

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil 

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved