Mobil Delvac™ Extended Life 50/50 Prediluted Coolant/Antifreeze

Mobil Commercial Vehicle Lube , Ecuador

Mobil commercial-vehicle-lube, Ecuador

Product Description

Mobil Delvac Extended Life 50/50 Prediluted Coolant/Antifreeze is a ready to use phosphatefree, silicatefree, nitritefree and boratefree ethylene glycol base coolant that is designed to provide exceptional wet sleeve liner cavitation and corrosion protection of all cooling system metals.

Mobil Delvac Extended Life 50/50 Prediluted Coolant/Antifreeze is formulated with organic corrosion inhibitors to provide total cooling system protection for 1,000,000 miles of onroad use (8 years or 20,000 hours of offhighway use). Since the organic corrosion inhibitors do not readily deplete, Mobil Delvac Extended Life 50/50 Prediluted Coolant/Antifreeze eliminates the need for Supplemental Coolant Additives (SCAs) as required when using conventional coolants.

Mobil Delvac Extended Life 50/50 Prediluted Coolant/Antifreeze is a 50/50 mix of Mobil Delvac Extended Life Coolant/Antifreeze and deionized water.

Features and Benefits

- Long Service Life: 1,000,000 miles of onroad use (8 years or 20,000 hours of offhighway use)
- Designed for use in engines running EGR and SCR technologies that can increase cooling system temperatures
- Eliminates the cost of SCAs, test strips and manpower required to test the coolant and add SCAs
- Can accept up to 25% mixing with conventional coolant technologies, with no detrimental effect to corrosion protection or reducing the extended life properties
- Fully compatible with other quality Organic Acid (OAT) and Nitrited Organic Acid (NOAT) heavy-duty extended life coolants
- Nonabrasive formula can improve water pump seal life
- Optimal hard water compatibility and reduced hard water scale
- Provides outstanding long-term elastomer compatibility

Applications

Mobil Delvac Extended Life 50/50 Prediluted Coolant/Antifreeze is recommended by ExxonMobil for use in:

- All types of heavyduty diesel, gasoline and natural gas engines.
- Stationary engine applications regardless of fuel type being used.
- Marine cooling systems where freeze protection is needed.
- Mixed fleets where both lightduty and heavyduty trucks are present.

Specifications

Mobil Delvac™ Extended Life Coolant/Antifreeze is recommended by ExxonMobil for use in applications requiring:

- ASTM D 6210
- Detroit Fluid Specification 93K217
- MTU 5048
- ASTM D 7583
- John Deere H24A2, H24C2
- Navistar CEMSB1Type IIIa
- Behr Radiator
- MAN 324 Type SNF
- TMC RP 329
- CAT EC1
- Cummins CES 14603

- **Meets the performance requirements of:**
- Volvo/Mack
- Paccar
- Phosphatefree requirements of European original equipment manufacturers (OEMs)
- Silicatefree requirements of Japanese OEMs

Protection Table

Concentration	**Protects from**	
	Freezing Down to	**Boiling up to***
50	-37 °C / -34°F	129 °C / 265 °F

*Using a 15 PSI Pressure Cap

Chemical Properties

Property	**ASTM Test Method**	**Typical Values**
Specific Gravity (60/60˚F)	D1122	1.070 – 1.090
Freezing Point, 50 Vol. %, ˚F	D3321 or D1177	-34˚F
Boiling Point, 50 Vol. %, ˚F	D1120	226˚F
pH, 50% Volume Solution	D1287	8.0 – 9.0
Reserve Alkalinity, mL	D1121	3.8 – 5.0
Foam Test	D1881	150 ml. / 5 sec., Max
Color	Visual	Red

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2025

Terpel-Lubricantes Ecuador S.A.S

Av. Joaquin Orrantia 125 y Av. de las Américas, Edificio Solaris, Piso 12, Oficinas 801-812, Guayaquil, Ecuador

Teléfono: (593) 4-3811980

Las características típicas son típicas de aquellas obtenidas con la tolerancia de la producción normal y no constituyen una especificación. Durante la fabricación normal y en los diferentes lugares de mezcla son esperadas variaciones que no afectan el desempeño del producto. La información aquí contenida está sujeta a cambios sin previo aviso. Todos los productos pueden no estar disponibles localmente. Para obtener más información, comuníquese con su representante local de ExxonMobil, o viste www.exxonmobil.com

ExxonMobil se compone de numerosas filiales y subsidiarias, muchas de ellas con nombres que incluyen Esso, Mobil o ExxonMobil. Nada en este documento está destinado a invalidar o sustituir la separación corporativa de entidades locales. La responsabilidad por la acción local y la contabilidad permanecen con las entidades locales afiliadas a ExxonMobil.

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved