



## Mobil Delvac™ City Logistics P 5W-30

Mobil Commercial Vehicle Lube , Spain

Synthetic Light Commercial Vehicle Engine Oil

### Product Description

Mobil Delvac™ City Logistics P 5W-30 is a low ash synthetic engine oil that provides long engine life and excellent engine protection against sludge & wear.

Mobil Delvac™ City Logistics P 5W-30 provides excellent lubrication of diesel and gasoline engines operating in severe driving conditions typically encountered in city operations. This product is recommended by ExxonMobil for European engines for use in a wide range of light-duty commercial vehicles like Peugeot-Citroen but also Iveco and Fiat vans requiring to meet or exceed the requirements of ACEA C2

### Features and Benefits

Mobil Delvac™ City Logistics P 5W-30 is formulated from high performance base oils and a superior balanced additive system to provide optimum engine performance in recent diesel and gasoline engines as well as older models: It is fully compatible with most Diesel Particulate Filters and Catalytic Convertors. Key benefits include:

| Features   | Advantages and Potential Benefits   |
|--|---|
| Increased thermal and oxidation stability  | Help to reduced sludge build-up, deposits, and long oil and engine life         |
| Enhanced wear protection   | Helps towards long component and engine life                                    |
|  |   |
| Advanced piston deposit control  | Helps to keep engines clean with reduced maintenance costs and long engine life |
| Advanced soot handling to control viscosity increase, sludge build up, and filter pressure | Helps to enhance engine protection for long engine life                         |
| Enhanced low temperature pumpability   | Fast start up with reduced wear operating in low temperature climates           |
| Stayed in viscosity grade  | Helps to maintain fuel economy  |

### Applications

ExxonMobil recommends Mobil Delvac™ City Logistics P 5W-30 for demanding driving conditions:

- Peugeot-Citroen vans
- Iveco and Fiat vans requiring ACEA C2
- Gasoline and Diesel with Diesel Particulate Filters (DPF) and Catalytic Convertors
- Normal to occasionally severe operating conditions (including city driving conditions)

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

| Mobil Delvac™ City Logistics P meets or exceeds the requirements of: | 5W-30 |
|--|-------|
| ACEA C2  | X     |
| API SN   | X     |

| Mobil Delvac™ City Logistics P has the following builder approvals: | 5W-30 |
|---|-------|
| Peugeot-Citroen B712290   | X     |

## Typical Properties

| Mobil Delvac™ City Logistics P 5W-30   |       |
|--|-------|
| Viscosity                              | 5W-30 |
| mm <sup>2</sup> /s @ 40°C, ASTM D 445  | 56    |
| mm <sup>2</sup> /s @ 100°C, ASTM D 445 | 10,3  |
| Sulfated Ash, wt%, ASTM D 874          | 0,78  |
| Total Base, mg KOH/g, ASTM D 2896      | 8     |
| Flash Point, °C, ASTM D 92             | 232   |
| Density @15° C kg/l, ASTM D 4052       | 0,85  |
| Pour Point, °C, ASTM D 97              | -36   |

## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Mobil, Mobil Delvac 1, the Mobil logotype, and the Pegasus design are trademarks or registered trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

09-2023

ExxonMobil Lubricants and Specialties Europe division of ExxonMobil Petroleum & Chemical b.v.b.a.

Polderdijkweg


B-2030 Antwerpen, Belgium

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved