



Mobil Coolant Extra Ready Mixed -24°C

Mobil Ancillary , Fiji

Extra High Performance Coolant

Product Description

Mobil Coolant Extra Ready Mixed -24°C is an extra performance coolant designed to provide efficient protection during cold conditions in temperature as low as -24°C. It is a ready-to-use product that has been premixed with 36% Mobil Antifreeze Extra and 64% water.

Applications

Mobil Coolant Extra Ready Mixed -24°C contains Glysantin from BASF. Glysantin® G48® by BASF approved by:

Audi/Seat/Skoda/VW (vehicles built up until 1996) TL 774-C, Porsche (vehicles built up until 1998) TL 774-C, Rolls-Royce (vehicles built as from 1998), BMW N 600 69.0, MAN 324 NF, Mercedes-Benz specifications 325.0, MTU MTL 5048, Opel/Vauxhall (vehicles built up until 2000) B 040 0240, Saab 690 1599.

Pour into vehicle cooling system as recommended by vehicle manufacturer. Mobil Coolant Extra Ready Mixed -24°C should not be mixed with silicate free, OAT engine coolants. Most coolant blends are based on carefully balanced mixtures of various corrosion inhibitors. Mixing of coolants with different inhibitor packages can lead to loss of corrosion protection.

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2023

ExxonMobil

Exxon

Mobil



© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved