



Mobil Delvac XHP™ 15W-40

Mobil Commercial Vehicle Lube , France

High Performance Diesel Engine Oil

Product Description

Mobil Delvac XHP™ 15W-40 is a high performance diesel engine oil that provides protection for diesel engines operating under severe service conditions for both on- and off-highway applications. Mobil Delvac XHP 15W-40 is recommended by ExxonMobil for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

Features and Benefits

| Features | Advantages and Potential Benefits |
|-----------------------------------|--|
| Thermal and oxidation stability | Helps to control sludge build-up and deposits |
| TBN reserve | Helps to control deposits |
| Stay-in-grade shear stability | Helps to reduce oil consumption and to provide wear protection |
| Excellent detergency/ dispersancy | Helps to protect and to maintain engines clean |
| Component compatibility | Long gasket and seal life |

Applications

- Naturally aspirated and turbo-charged diesel powered equipment of European, Japanese and American manufacturers in line with owner manual recommendations
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying and agriculture

Specifications and Approvals

| This product has the following approvals: |
|---|
| MTU Oil Category 1 |

| This product is recommended for use in applications requiring: |
|--|
| ACEA B2 |
| API SH |
| MAN M 3275-1 |

This product is recommended for use in applications requiring:

RENAULT TRUCKS RD

RENAULT TRUCKS RD-2

RENAULT TRUCKS RLD

VOLVO VDS-2

This product meets or exceeds the requirements of:

API CH-4

Properties and Specifications

| Property | |
|--|------------|
| Grade | SAE 15W-40 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 110 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 14.6 |
| Density @ 15 C, lb/USg, ASTM D4052 | 0.87 |
| Total Base Number, mgKOH/g, ASTM D2896 | 9.2 |
| Viscosity Index, ASTM D2270 | 136 |
| Ash, Sulfated, mass%, ASTM D874 | 1.1 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 225 |
| Pour Point, °C, ASTM D97 | -36 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2024

Esso Société Anonyme Française

20 rue Paul Héroult
92000 Nanterre, France

Société Anonyme au capital de 98 337 521,70 euros

RCS Nanterre 542 010 053

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.fr/fr-fr/contact-us>

Tel. +33 (0)1 49 67 90 00

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil 

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved