



MOBIL SPECIAL

Mobil Passenger Vehicle Lube , Guyana

Synthetic Blend Motor Oil

Product Description

Mobil Special™ motor oils are formulated from quality base stocks combined with modern performance additives to provide the engine protection and performance you expect under a wide variety of operating conditions. Mobil Special motor oils come with the Mobil Limited Warranty*. Mobil Special oils meet warranty requirements where an American Petroleum Institute (API) certified oil is specified.

Features and Benefits

Mobil Special™ motor oils are formulated from quality base stocks combined with modern performance additives to provide the engine protection and performance you expect under a wide variety of operating conditions.

Key features and potential benefits include:

Features	Advantages and Potential Benefits
Meets or exceeds the latest industry specifications	OEM warranty protection
Engine cleansing agents	Helps prevent the formation of sludge and deposits
Modern performance additives	Reduces wear and corrosion
Warranty	Mobil Special Limited Warranty*
Tested, proven engine protection	Protects under a wide variety of operating conditions

Applications

Mobil Special™ motor oils are recommended by ExxonMobil for all types of modern gasoline-powered engines found in passenger cars, SUVs, light vans and light trucks.

- Mobil Special motor oils meet warranty requirements where an American Petroleum Institute (API) certified oil is specified.
- Mobil Special is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

Always check your owner's manual for the manufacturer's recommended oil viscosity grade, API service classification and any builder approval.

Specifications and Approvals

This product is recommended for use in applications requiring:	5W-20	5W-30*	10W-30*	10W-40	20W-50
Ford WSS-M2C930-A	X				
Ford WSS-M2C945-A	X				
Ford WSS-M2C945-B1	X				

This product is recommended for use in applications requiring:	5W-20	5W-30*	10W-30*	10W-40	20W-50
Ford WSS-M2C946-A		X			
Ford WSS-M2C946-B1		X			
Ford WSS-M2C929-A		X			
GM 6094M	X	X	X		

This product meets or exceeds the requirements of:	5W-20	5W-30*	10W-30*	10W-40	20W-50
API SJ	X	X	X		X
API SL	X	X	X	X	X
API SM	X	X	X	X	X
API SN	X	X	X	X	X
API SN PLUS	X	X	X	X	X
API SN PLUS RESOURCE CONSERVING	X	X	X		
API SN Resource Conserving	X	X	X		
API SP	X	X	X	X	X
API SP Resource Conserving	X	X	X		
API SQ	X	X	X		
API SQ Resource Conserving	X	X	X		
ILSAC GF-6A	X	X	X		
ILSAC GF-7A	X	X	X		
Chrysler MS-6395	X	X	X		
FORD WSS-M2C960-A1	X				
FORD WSS-M2C961-A1		X			

Properties and Specifications

Property	5W-20	5W-30*	10W-30*	10W-40	20W-50
Grade	SAE 5W-20	SAE 5W-30	SAE 10W-30	SAE 10W-40	SAE 20W-50
Density @ 15 C, g/ml, ASTM D4052					0.874
Density @ 15.6 C, g/ml, ASTM D4052	0.859	0.859	0.858	0.867	
Flash Point, °C, ASTM D92					252

Property	5W-20	5W-30*	10W-30*	10W-40	20W-50
Flash Point, Cleveland Open Cup, °C, ASTM D92	216	228	226		
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	8.3	10.3	10.3	15.7	19.5
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	49	63	64	113	167
Pour Point, °C, ASTM D97	-42	-39	-39	-39	-27

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2026

ExxonMobil

Exxon Mobil 

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved