Mobil

Mobil SHC™ Gear OH Series

Mobil Industrial , Indonesia

Exceptional Performance Gear Oils for Off-Highway Equipment

Product Description

The Mobil SHC™ Gear OH Series lubricants are exceptional performance heavy-duty gear oils primarily designed to lubricate enclosed gearing as well as plain and rolling element bearings in off-highway equipment subject to shock and heavy loading. They are designed to provide outstanding service in terms of equipment protection, oil life, and problem-free operation helping to enable increased customer productivity. These scientifically engineered synthetic lubricants are formulated from synthetic base fluids that have exceptional oxidation and thermal properties and excellent low temperature fluidity. The combination of a naturally high viscosity index and a unique additive system helps enable these products to provide outstanding performance under severe high and low temperature operating conditions. The nature of the synthetic base fluids also contributes to the products' excellent low temperature performance. They deliver outstanding gear scuffing protection in heavily loaded gearboxes. The synthetic base stocks have inherently low traction properties that result in low fluid friction in the load zone of non-conforming surfaces such as gears and rolling element bearings. Reduced fluid friction produces lower operating temperatures and improved gear efficiency. The Mobil SHC Gear OH Series is available in viscosity range from ISO VG 320 to 680, and are the products of choice for key OEMs and customers for demanding off-highway applications.

Features and Benefits

The Mobil SHC Gear OH Series of lubricants is a member of the Mobil SHC brand of products. These scientifically engineered synthetic lubricants symbolize the continuing commitment to using advanced technology to provide outstanding lubricant products. The Mobil SHC Gear OH Series of lubricants provide benefits not possible with mineral stocks, particularly under extreme high and low temperature operating conditions.
Our formulation scientists have used a proprietary additive combination that fortifies the base fluids to provide excellent EP and anti-wear performance that protects equipment, even under heavy load situations. Specific features and potential benefits for the Mobil SHC Gear OH Series of lubricants include:

Features	Advantages and Potential Benefits
Outstanding load-carrying and antiwear properties	Helps extend gear life and reduce maintenance costs
High viscosity index	Trouble-free operation over a wide temperature range particularly at extremely low temperatures.
Low traction properties	Helps improve gear efficiency and lower operating temperatures lead to lower operating costs
Outstanding thermal/oxidation resistance and long product life	Helps reduce lubricant consumption, which can reduce product and change-out costs
Light color	Helps minimize the need for gear cleaning prior to inspections, which can reduce maintenance costs

Applications

Application Considerations: While the Mobil SHC Gear OH Series are compatible with mineral oil based products, admixture may detract from their performance. Consequently it is recommended that before changing a system to one of the Mobil SHC Gear OH Series, it should be thoroughly cleaned out and flushed to achieve the maximum performance benefits.

Mobil SHC Gear OH Series oils are recommended for many types of enclosed steel-on-steel gear drives. They are suitable for both circulation and splash lubrication systems. Mobil SHC Gear OH Series is available in viscosities from ISO 320 to ISO 680, providing the right lubrication option for low temperature applications where pour points as low as -45°C (-49°F) are required to high temperature applications where operating temperatures of 121ºC (250ºF) are encountered. They are particularly recommended for lubricating gear sets in off-highway applications such as those found in mining, where heavy or shock loads and boundary lubrication conditions may prevail.

Specifications and Approvals

This product has the following approvals:	460	680
GE OHV D50E35A/B/C/D/E		X

This product meets or exceeds the requirements of:	460	680
AGMA 9005-F16	X	X

Properties and Specifications

Property	320	460	680
Grade	ISO VG 320	ISO VG 460	ISO VG 680
ASTM Color, ASTM D1500	L0.5	L0.5	L0.5
Brookfield Viscosity @ -28.9 C, mPa.s, ASTM D2983	60000	110000	170000
Copper Strip Corrosion, 3 h, 100 C, Rating, ASTM D130	1B	1B	1B
Density @ 15.6 C, kg/l, ASTM D4052	0.86	0.86	0.86
FZG Scuffing, Fail Load Stage, A/8.3/90, ISO 14635-1(mod)	>13	>13	>13
Flash Point, Cleveland Open Cup, °C, ASTM D92	233	233	233
Foam, Sequence I, Stability, ml, ASTM D892	0	0	0
Foam, Sequence I, Tendency, ml, ASTM D892	0	0	0
Foam, Sequence II, Stability, ml, ASTM D892	0	0	0
Foam, Sequence II, Tendency, ml, ASTM D892	0	0	0
Foam, Sequence III, Stability, ml, ASTM D892	0	0	0
Foam, Sequence III, Tendency, ml, ASTM D892	0	0	0
Four-Ball Extreme Pressure Test, Load Wear Index, kgf, ASTM D2783	62	62	62
Four-Ball Extreme Pressure Test, Weld Load, kgf, ASTM D2783	250	250	250
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	40.1	54.9	76.1
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	320	460	680
Pour Point, °C, ASTM D5950	-45	-42	-39
Rust Characteristics, Procedure B, ASTM D665	PASS	PASS	PASS
Total Acid Number, mgKOH/g, ASTM D664	0.6	0.6	0.6
Viscosity Index, ASTM D2270	178	186	193

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2026

ExxonMobil Asia Pacific Pte Ltd
Jakarta Representative Office
Wisma GKBI 27th Floor
Jl. Jenderal Sudirman No. 28
Jakarta 10210
Indonesia

+62 21 574 0707
http://www.exxonmobil.com

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved