



Mobil Super™ Friction Fighter 15W-40

Mobil Passenger Vehicle Lube , Indonesia

Mobil passenger-vehicle-lube, Synthetic Technology, Indonesia

Product Description

Mobil Super™ Friction Fighter 15W-40 is brought to you by the makers of Mobil 1™. This synthetic technology engine oil is specially engineered with enhanced engine wear protection to prolong your engine life.

It is formulated with Friction Fighter™ molecules to create a solid protective layer that cushions the impact when engine parts come in contact, protecting your engine against life-shortening wear.

Features and Benefits

- Proprietary Friction Fighter™ molecules
- Outstanding wear protection for long engine life
- Excellent high temperature protection under severe operating conditions

Applications

Mobil Super™ Friction Fighter 15W-40 is suitable for use in the diesel pickup trucks, SUVs, vans, and cars from leading Japanese, European, and American manufacturers.

Mobil Super™ Friction Fighter Diesel Turbospeed 15W-40 is also recommended for turbo-charged and common rail diesel engines.

Always consult your owner's manual to check the recommended viscosity grade and specifications for your particular vehicle.

This product is recommended for use in applications requiring:
API CF
This product meets or exceeds the requirements of:
API SM
API SN
API SN PLUS
ACEA A3/B3-16

Properties and Specifications

Property	
Grade	SAE 15W-40
Mini-Rotary Viscometer, Apparent Viscosity, -25 C, mPa.s, ASTM D4684	14600
Pour Point, °C, ASTM D97	-39
Flash Point, Cleveland Open Cup, °C, ASTM D92	239
Ash, Sulfated, mass%, ASTM D874	0.9
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.9

Property	
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	104
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.5
Density @ 15.6 C, g/ml, ASTM D4052	0.873
Total Base Number, mgKOH/g, ASTM D2896	9.9
Viscosity Index, ASTM D2270	143

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2025

ExxonMobil Asia Pacific Pte Ltd
 Jakarta Representative Office
 Wisma GKBI 27th Floor
 Jl. Jenderal Sudirman No. 28
 Jakarta 10210
 Indonesia

+62 21 574 0707

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved