Mobilgrease MP 3

Mobil Grease , India

Lithium Automotive Grease

Product Description

Mobilgrease MP 3 is a high quality, multipurpose, NLGI 3grade, lithium grease based on an ISO VG 160 mineral oil. It is formulatedto provide added protection against rusting and water washout in general purposeautomotive applications at moderate temperatures and loads.

Features and Benefits

Mobilgrease MP 3 has a long history of proven performance ingeneral purpose automotive applications and provides the following benefits:

- Wide operating temperature range
- Good resistance to water washout
- Extra protection against rust and corrosion
- Excellent structural stability
- Lead, chlorine and nitrite free

Applications

Mobilgrease MP 3 is recommended for the lubrication of automotive chassiscomponents, wheel bearings, clutch bearings, universal joints and balljoints of steering and suspension systems of passenger cars, trucks, farmtractors and most other types of mobile equipment operating under moderateconditions. The recommended operating temperature range ofMobilgrease MP 3 is -20ºC to 120ºC. In applications where heavy orshock loading is a factor, extreme pressure greases are preferred.

Typical Properties

Mobilgrease MP 3	Test Method	Unit	
NLGI Grade	ASTM D 217		3
Soap Type			Lithium
Color	Visual		Medium Brown
Structure	Visual		Smooth
Penetration, Worked	ASTM D 217	0.1 mm	235
Dropping Point	ASTM D 2265	ºC	180
Viscosity of Oil @ 40ºC	ASTM D 445	cSt	160
-	-	-	-

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

09-2019

ExxonMobil Services & Technology Private Limited
(CIN: U74900KA2015FTC080245)
Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,
Whitefield Main Road, Bangalore – 560048, Karnataka, India

+918071085300
http://www.exxonmobil.com

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved