



## Mobil Super™ Friction Fighter Taxi 5W-30

Mobil Passenger Vehicle Lube , India

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

### Product Description

Mobil Super™ Friction Fighter Taxi is brought to you by the makers of Mobil 1. This synthetic technology engine oil is specially engineered to enhance engine wear protection to prolong your engine life.

It is specifically formulated with FrictionFighter™ molecules to create a solid protective layer that cushions the impact when engine parts come in contact, protecting your engine against life-shortening wear.

### Features and Benefits

- Excellent engine wear protection
- Improved fuel economy (as per ACEA A5/B5)
- Enhanced engine cleanliness and sludge prevention

### Applications

Mobil Super™ Friction Fighter Taxi is recommended for use in petrol, diesel and CNG vehicles operating in normal to severe conditions.

### Specifications and Approvals

<b>This product is recommended for use in applications requiring:</b>
API CF

<b>This product meets or exceeds the requirements of:</b>
API SL
API SN Engine Test Requirements

### Properties and Specifications

Property	
Grade	SAE 5W-30
Pour Point, °C, ASTM D97	-39
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	18800
Flash Point, °C, ASTM D92	222

Property	
Ash, Sulfated, mass%, ASTM D874	1.1
Density @ 15 C, g/ml, ASTM D4052	0.85
Total Base Number, mgKOH/g, ASTM D2896	10.6
Viscosity Index, ASTM D2270	172
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	52
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	9.6
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	2.9

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

Synthetic Technology Engine Oil

07-2024

ExxonMobil Services & Technology Private Limited

(CIN: U74900KA2015FTC080245)

Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,

Whitefield Main Road, Bangalore – 560048, Karnataka, India

+918071085300

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved