



Mobil Super™ 3000 Formula P 0W-30

Mobil Passenger Vehicle Lube , Iceland

High Performance Motor Oil

Product Description

Mobil Super 3000 Formula P 0W-30 is specially developed to meet Stellantis requirements for diesel and gasoline engines complying with Euro 6 emission standards. Mobil Super 3000 Formula P 0W-30 is a low ash, high-performance engine oil designed to help prolong the life and maintain the efficiency of car exhaust emission reduction systems in both diesel and gasoline-powered automobiles, and bring fuel economy benefits when switching from higher 5W-30 viscosity oils.

Features and Benefits

Mobil Super 3000 Formula P 0W-30 delivers excellent high and low temperature wear protection for extended engine life.

- Low ash, low phosphorus, and low sulfur formulation helps maintain the efficiency of emission reduction systems in both diesel and gasoline-powered engines.
- Oil fluidity helps reduce fuel consumption (as per ACEA C2), which contributes to reducing greenhouse gas (CO2) emissions.
- Excellent low temperature capabilities for reliable cold weather starts, allowing fast engine and electrical system protection.
- Active cleaning agents prevent deposits and sludge build-up, and the high-performance wear protection system contributes to a long engine life.
- Excellent low temperature capabilities for reliable cold weather starting allowing fast engine and electrical system protection.
- High performance wear-protection.
- Active cleaning agents reducing deposits and sludge build-up to enable long and clean engine life.

Applications

Mobil Super 3000 Formula P 0W-30 is designed for Stellantis Euro 6 diesel and gasoline engines requiring a 0W-30 viscosity oil, specifically those that call for any of the claims met by the oil (refer to Product Specifications & Approvals). Mobil Super 3000 Formula P 0W-30 particularly meets the latest Stellantis FPW9.55535/DH1 0W-30 specification but also PSA B 71 2312 specification. Car & Light Duty Vehicle brands under the Stellantis group that require Mobil Super 3000 Formula P 0W-30 include Peugeot, Citroën, Fiat, Opel, Vauxhall, among others. Always consult your owner's manual to check the recommended oil viscosity grade and specifications for your vehicle.

Specifications and Approvals

This product has the following approvals:

PSA B71 2312

PSA B71 2302

FPW9.55535/DH1

This product meets or exceeds the requirements of:

FIAT FIAT 9.55535-GS1

ACEA C2

This product meets or exceeds the requirements of:

FIAT FIAT 9.55535-DS1

Properties and Specifications


Property	
Grade	SAE 0W-30
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	9.7
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	51.8
Density @ 15.6 C, g/ml, ASTM D4052	0.84
Pour Point, °C, ASTM D97	-42
Flash Point, Cleveland Open Cup, °C, ASTM D92	234
Ash, Sulfated, mass%, ASTM D874	0.5
Phosphorus, mg/kg, ASTM D5185	0.08

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2025

© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved