Mobil

# Mobil 1™ 0W-40

Mobil Passenger Vehicle Lube , Kenya

Advanced Full Synthetic Motor Oil

**Product Description**

Mobil 1™ is the world's leading synthetic motor oil brand delivering our ultimate performance and protection.

Mobil 1™ 0W-40 Advanced Full Synthetic Motor Oil is engineered for the latest gasoline and diesel (without Diesel Particulate Filters or DPFs) engine technology delivering excellent all-round performance. It provides exceptional cleaning power, wear protection and overall performance. Mobil 1 0W-40 keeps your engine running like new in all driving conditions.

**Features and Benefits**

Mobil 1 0W-40 is made with a proprietary blend of ultra high performance synthetic basestocks fortified with a precisely balanced component system.

•Meets or exceeds the latest OEM and industry approvals

•Is chosen for factory fill in many of the world's finest vehicles

•Provides excellent overall performance

•Has excellent low temperature capabilities for rapid engine protection at start-up

•Has enhanced frictional properties that aids fuel economy

•Delivers fast protection for reduced engine wear and deposits even in the most extreme driving conditions

•Provides exceptional cleaning power for dirty engines

**Applications**

Thanks to extensive cooperative development work with major manufacturers and the application of the latest lubrication technology, Mobil 1 0W-40 is recommended for many types of modern vehicles where it will help provide unsurpassed performance even under very demanding driving conditions.

•Latest engine technologies including Turbo-chargers, Direct Injection, Diesels (without DPF) and Hybrids

•High performance engines

•Most operating conditions, from mild to extreme

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

**Specifications and Approvals**

| This product has the following approvals: |
|---|
| MB-Approval 229.3 |
| MB-Approval 229.5 |
| Nissan Genuine Performances |
| VW 502 00 |
| VW 505 00 |

| This product is recommended for use in applications requiring: |
|---|
| API CF |
| FIAT 9.55535-M2 |
| VW 503 01 |

| This product meets or exceeds the requirements of: |
|---|
| API SJ |
| API SL |
| API SM |
| API SN |
| ACEA A3/B3 |
| ACEA A3/B4 |
| Ford WSS-M2C937-A |

**Properties and Specifications**

| Property | |
|---|---|
| Grade | SAE 0W-40 |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 12.9 |
| Density @ 15 C, g/cm3, ASTM D4052 | 0.846 |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445 | 71 |
| Ash, Sulfated, mass%, ASTM D874 | 1.34 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 226 |
| Viscosity Index, ASTM D2270 | 185 |

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2026
Mobil Oil Kenya Ltd.
P.O. Box 64900 - 00620, Nairobi

+ 254 2 3767842-9

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without

notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved