Mobil

Mobil Super™ 3000 XE3 5W-30

Mobil Passenger Vehicle Lube , Cambodia

Fully Synthetic Engine Oil delivering All-In-One Protection

Product Description

Mobil Super 3000 XE3 5W-30 All-In-One Protection is a low ash high performance motor oil designed to help prolong the life and maintain the efficiency of the Exhaust Car Emission Reduction Systems in both diesel and gasoline powered automobiles.

It is formulated with Heat Activated Anti-Wear™ molecules for superior engine protection in high temperature while keeping your engine clean.

This product is recommended for use in Mercedes vehicles and a wide range of European cars and light-duty commercial vehicles with oil specifications built on the ACEA C3 and/or API SN industry baseline.

Features and Benefits

• Helps maintain the efficiency of the exhaust emission reduction systems in both diesel and gasoline vehicles.

• Permits extended operation at elevated temperatures without oxidative oil thickening and oil breakdown.

• Provides excellent fluidity at low temperatures allowing easy winter starting and rapid oil circulation around the engine.

• Long term engine protection from wear and sludge and deposit build-up

• Suitable for use in both gasoline and diesel engine passenger car and light commercial vehicles

Applications

Mobil Super 3000 XE3 5W-30 All-In-One Protection has been developed to meet the latest specifications for engine oils required by major car manufacturers and is compatible with the latest Gasoline and Diesel Particulate Filters and catalytic converters.

Mobil Super 3000 XE3 5W-30 is specially recommended by ExxonMobil for use in:

- Mercedes and General Motors passenger cars and light commercial vehicles or vans requiring ACEA C2/C3 and/or API SN
- Gasoline and Diesel with Diesel Particulate Filters (DPF) & Catalytic Convertors.
- Normal to occasionally severe operating conditions including city driving conditions.

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:
GM dexos2
MB-Approval 229.51

This product has the following approvals:
RENAULT RN0700
RENAULT RN0710

This product is recommended for use in applications requiring:
API CF
Ford WSS-M2C917-A

This product meets or exceeds the requirements of:
API SM
API SN

Properties and Specifications

Property	
Grade	SAE 5W-30
Viscosity Index, ASTM D2270	170
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	11.9
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.5
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	69
Flash Point, Cleveland Open Cup, °C, ASTM D92	234
Ash, Sulfated, mass%, ASTM D874	0.8
Total Base Number, mgKOH/g, ASTM D2896	8
Pour Point, °C, ASTM D97	-33
Density @ 15 C, kg/l, ASTM D4052	0.8516
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	32600

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2026

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved