



## Mobil Super™ All-In-One Protection 0W-20

Mobil Passenger Vehicle Lube , Mongolia

Full Synthetic Engine Oil

### Product Description

Mobil Super™ All-In-One Protection 0W-20 is brought to you by the makers of Mobil 1. This full synthetic engine oil is tailored to deliver improved fuel economy by up to 10%\* and provides outstanding engine wear protection even under the most demanding driving conditions.

Mobil Super™ All-In-One Protection 0W-20 is formulated with Heat Activated Anti-Wear™ molecules technology which provides superior engine protection under high temperature and proven protection for 20 years.\*

Mobil Super™ All-In-One Protection 0W-20 is proven during API SQ engines test to reduce damaging Low Speed Pre-Ignition (LSPI) problem in modern engines. This helps to improve engine efficiencies and prolong engine life.

### Features and Benefits

- Suitable for gasoline engines
- Heat Activated Anti-Wear Molecule provides high temperature wear protection while keeping your engine clean
- Proven protection for 20 years
- 10% Improvement in fuel economy performance
- Fights sludge with active cleaning agents \*\*\*

\* Based on Sequence VIE test results vs. API SQ engine test requirement. Performance may vary depending on the engine design, fuel, temperature and actual driving conditions.

\*\*Based on field trail in USA under controlled test conditions with routine oil change. 20 Years is based on annual driving distance 16,000 km. Performance may vary depending on the engine design, fuel, temperature and actual driving conditions.

\*\*\* Based on passing Sequence VH engine test.

### Applications

Mobil Super™ All-In-One Protection 0W-20 is suitable for use in the gasoline engines.

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

This product meets or exceeds the requirements of:
ILSAC GF-6A
API SJ
API SL

<b>This product meets or exceeds the requirements of:</b>
API SM
API SN
API SN PLUS
API SP
Ford WSS-M2C947-A
Ford WSS-M2C947-B1
FORD WSS-M2C962-A1
API SQ
ILSAC GF-7A

## Properties and Specifications

<b>Property</b>	
Grade	SAE 0W-20
Ash, Sulfated, mass%, ASTM D874	0.8
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	45
Density @ 15.6 C, g/ml, ASTM D4052	0.847
Total Base Number, mgKOH/g, ASTM D2896	7.5
Flash Point, Cleveland Open Cup, °C, ASTM D92	220
Pour Point, °C, ASTM D97	-42
Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684	24700
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	2.6
Viscosity Index, ASTM D2270	170
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	8.5

## Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2025



© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved