



## Mobil Super™ Extengine 10W-30

Mobil Passenger Vehicle Lube , Mexico

### Product Description

Mobil Super Extengine are synthetic technology motor oils designed to help maintain a high level of performance and protection under most operating conditions, renewing and extending the good conditions of your engine for up to 5 years\* and offering proven protection for 200,000KM\*\*, providing long engine life for vehicles with typically more than 65,000 km.

Mobil Super Extengine SERIES oils are meticulously engineered for today's tougher engine specifications, they contain Extengine™ to create a renovating layer on the metal surfaces that helps normalize their shape and reduce wear. By retarding the aging process, Mobil Super Extengine SERIES are oil contribute to extend your engine's life.

These motor oils are classified by API as "Resource Conserving" engine lubricants, and meet or exceed the latest industry specification ILSACGF-7A / API SQ .

Those claims are backward compatible with earlier performance levels such as API SQ, SN, SM, SL and SJ and previous ILSAC categories.

### Features and Benefits

Helps protect engines with typically more than 65,000 km

Outstanding wear protection under a wide variety of operating conditions

Easy cold starting

Meets or exceeds the latest industry specification (ILSAC GF-7A /APISQ)

API SQ / Resource Conserving

Excellent protection against low-speed pre-ignition for turbo charged direct injection gasoline-powered vehicles

\*The years of extension in the engine's life are based on field trials using real life driving conditions and on the road vehicles, considering commonly annual miles traveled by passenger vehicles in Mexico.

The field trials referred to: Extending 5 more years the good conditions of the engine's life, when switching from any other SQ category approved Mobil gasoline engine oil (that was used for the first 5 years of the engine's life at a 13,000 Km ODIs) to Mobil Super Extengine.

\*\*Better wear protection compared to API SP engine test requirement in ASTM Seq. IVB test

\*\*\*Road test including severe service and stop and go driving cycles

### Applications

Mobil Super Extengine SERIES oils are recommended for current and earlier gasoline fueled passenger cars, sport utility vehicles, vans and light duty trucks requiring an API SQ, SP, SN, SM, SL or SJ. They also meet ILSAC GF-7A (Starburst Certification Symbol).

Before using Mobil Super Extengine SERIES motor oils, consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and API

Service Classification.

**Specifications and Approvals****This product is recommended for use in applications requiring:**

GM 6094M

**This product meets or exceeds the requirements of:**

API SJ

API SL

API SM

API SN

API SN PLUS

API SN PLUS RESOURCE CONSERVING

API SN Resource Conserving

API SP

API SP Resource Conserving

API SQ

API SQ Resource Conserving

ILSAC GF-6A

ILSAC GF-7A

Chrysler MS-6395

**Properties and Specifications**

Property	
Grade	SAE 10W-30
Pour Point, °C, ASTM D97	-36
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	10.3
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	65
Density @ 15.6 C, g/ml, ASTM D4052	0.861
Flash Point, Cleveland Open Cup, °C, ASTM D92	226

## Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2025

ExxonMobil Mexico, S.A. de C.V.

Poniente 146 No. 760 Col. Industrial Vallejo

C.P. 02300 Mexico, Ciudad de Mexico

(01 52) 55 5-333-9602 (01 52) 1-800-90-739-00

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved