Mobil

Mobil Delvac™ Super 1400 15W-40

Mobil Commercial Vehicle Lube , Malaysia

High Performance Diesel Engine Oil

Product Description

Mobil Delvac™ Super 1400 15W-40 is a high performance diesel engine oil that provides proven protection of diesel engines operating on and off- highway severe service applications. Mobil Delvac Super 1400 15W-40 is biodiesel compatible* and is recommended by ExxonMobil for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

Footnotes:

*based on CEC L-109-14 (test modified with palm B100), meeting the limits in ACEA E7-16

Features and Benefits

The technology in Mobil Delvac Super 1400 15W-40 delivers excellent performance in both

modern diesel engines as well as older models. The key benefits include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
TBN reserve	Deposit control
Stay-in-grade shear stability	Reduced oil consumption and wear protection
Excellent detergency/dispersancy	Cleaner engines and longer engine life
Component compatibility	Longer gasket and seal life

Applications

Recommended by ExxonMobil for use in:

• Naturally aspirated and turbo-charged diesel powered equipment of European,

Japanese, and American manufacturers

• On-highway light and heavy-duty trucking

• Off-highway industries including: construction, mining, quarrying, and agriculture

Specifications and Approvals

This product is recommended for use in applications requiring:
MAN M 3275-1
ACEA E3
API CF

This product is recommended for use in applications requiring:
API CF-4
API CG-4
API SJ
Mack EO-M
VOLVO VDS-2

Properties and Specifications

Property	
Grade	SAE 15W-40
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	14.7
Density @ 15.6 C, g/ml, ASTM D4052	0.880
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	108
Ash, Sulfated, mass%, ASTM D874	1
Flash Point, °C, ASTM D92	227
Viscosity Index, ASTM D2270	140
Total Base Number, mgKOH/g, ASTM D2896	9
Pour Point, °C, ASTM D97	-27

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2024
1-800-81-6233

SEALubeline@exxonmobil.com

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved