



Mobil Delvac Modern™ All Season Trans Fluid Series

Mobil Commercial Vehicle Lube , Peru

Mobil Commercial Vehicle Lubes

Product Description

Mobil Delvac Modern™ All Season Trans Fluid series has replaced the Mobiltrans™ AST series. There are no formulation changes thereby ensuring no impact on product compatibility or handling. Furthermore, there are no comingle restrictions on mixing products with old and new names. Technical claims and product performance remains unchanged.

Mobil Delvac Modern™ All Season Trans Fluid Series are high performing, multigrade drive train and hydraulic lubricants engineered to meet the extreme performance requirements in heavy-duty off-highway equipment. With three different viscosity grades available, each grade offers a wide operating temperature range suited for use in many climates, covering the viscosity requirements of multiple components including powershift transmissions, gearboxes, clutches, final drives, wet brakes and hydraulic systems.

Mobil Delvac Modern™ All Season Trans Fluid 20, Mobil Delvac Modern™ All Season Trans Fluid 30, (full synthetic lubricants) and Mobil Delvac Modern™ All Season Trans Fluid 40 (a semi-synthetic lubricant) combine selected high quality base oils and an advanced additive system to deliver the precise performance parameters needed to help maximize the productivity of construction, logging, mining and agriculture equipment operating in severe conditions.

These advanced technology lubricants are formulated for safe start-up at low temperatures while providing protection at elevated operating temperatures. They are especially designed for machines with electronic controls and to ensure long life and excellent performance for gears, bearings, seals and friction disc materials. Mobil Delvac Modern™ All Season Trans Fluid Series lubricants are formulated for excellent thermal and oxidation stability, and are designed to protect against deposit formation allowing them to last beyond typical OEM drain interval recommendations.

Features and Benefits

Today's technology has vastly improved the performance capabilities of heavy-duty off-highway equipment in terms of load, speed, control, reliability, and performance through innovative drive train designs. These designs have increased the requirements of drive train fluids to deliver higher performance, increased productivity and reduced operating costs. Friction control, wear protection, thermal stability, shear stability, rust and corrosion protection and seal compatibility are features of the drive train fluid that must be optimally balanced to provide extended clutch, gear and synchronizer life, smooth shift control and high load capability over a wide range of applications and operating conditions. Mobil Delvac Modern™ All Season Trans Fluid Series deliver exceptional performance in today's drive train components and hydraulic systems. The key benefits include:

Features	Advantages and Potential Benefits
Wide operating temperature performance	<ul style="list-style-type: none"> - Helps extend drain and service intervals over multiple seasons to lower operating costs and increase productivity - Excellent performance and responsiveness from critical components and reduce wear associated with cold start ups
Consolidate the number of fluids on your equipment	<ul style="list-style-type: none"> - Potential to use one fluid in multiple components to reduce the risks of misapplication and simplify your lubricant program - Multigrade performance reduces the number of viscosity grades required for use in different seasons, allowing you to extend drain intervals
Excellent frictional properties	<ul style="list-style-type: none"> - Outstanding clutch friction retention & slippage control & brake life - Excellent anti-chatter brake performance - Great hydraulic responsiveness
Exceptional shear stability	Maintains effective viscosity and film strength during severe operation

Features	Advantages and Potential Benefits
Excellent load carrying, anti-wear and EP performance	Great wear protection to help extend component life and reduce cost of operation
Compatible with clutch materials and elastomers	Long clutch component & seal life, reduced oil leakage
Protection from corrosion of copper and its alloys	Protects and extends the life of synchronizers
Formulated to ensure seal compatibility with most common seal materials used in off-highway equipment	Allows for longer seal life and compatibility with a variety of seal arrangements & materials
Outstanding protection against deposit formation	Help extend seal life, drain & service intervals
Superior thermal and oxidation stability	Long oil life, help reduce wear, extended equipment life
Excellent foam control protection	Excellent performance in wet brakes, hydraulic system

Applications

Mobil Delvac Modern™ All Season Trans Fluid Series are recommended for use in heavy-duty transmissions, gear boxes, differentials, final drives, wet brakes, and hydraulic systems.

Mobil Delvac Modern™ All Season Trans Fluid Series are suitable for use in equipment requiring Caterpillar TO-4 and TO-4M fluids and Komatsu equipment, requiring good micro-clutch performance.

Specifications and Approvals

According to ExxonMobil, this product is of the following quality level:	MOBIL DELVAC MODERN ALL SEASON TRANS FLUID 20	MOBIL DELVAC MODERN ALL SEASON TRANS FLUID 40
Allison C-4		X
KOMATSU KES 07.868.1		X

This product meets or exceeds the requirements of:	MOBIL DELVAC MODERN ALL SEASON TRANS FLUID 20	MOBIL DELVAC MODERN ALL SEASON TRANS FLUID 40
Caterpillar TO-4	X	
Caterpillar TO-4M		X

Properties and Specifications

Property	MOBIL DELVAC MODERN ALL SEASON TRANS FLUID 20	MOBIL DELVAC MODERN ALL SEASON TRANS FLUID 30	MOBIL DELVAC MODERN ALL SEASON TRANS FLUID 40
Grade	N/A	N/A	N/A
Brookfield Viscosity @ -30 C, mPa.s, ASTM D2983			45000

Property	MOBIL DELVAC MODERN ALL SEASON TRANS FLUID 20	MOBIL DELVAC MODERN ALL SEASON TRANS FLUID 30	MOBIL DELVAC MODERN ALL SEASON TRANS FLUID 40
Brookfield Viscosity @ -35 C, mPa.s, ASTM D2983		13400	
Brookfield Viscosity @ -40 C, mPa.s, ASTM D2983	5800		
Density @ 15.6 C, g/ml, ASTM D4052	0.8545	0.866	0.882
Flash Point, Cleveland Open Cup, °C, ASTM D92	190	190	222
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	7.36	10.5	14.2
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	30.7	57.6	107
Pour Point, °C, ASTM D97	-48	-48	-39
Viscosity Index, ASTM D2270	221	173	134

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2026

Terpel Comercial del Perú S.R.L.
Av. Jorge Basadre Grohmann 347,
Interior 1005, San Isidro
Lima, Perú
24 Horas emergencia en salud

LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved