



Mobil Super™ SemiSintetico 10W-40

Mobil Passenger Vehicle Lube , Peru

Synthetic Technology Oil for Passenger Vehicle Engines

Product Description

Mobil Super™ SemiSintetico 10W-40 is a synthetic technology oil that provides long engine life and protection against sludge and wear.

Features and Benefits

Mobil Super™ SemiSintetico 10W-40 is fully tested in the industry so you can have complete confidence that you will get the performance you want from your vehicle. Mobil Super™ SemiSintetico 10W-40 provides:

- Better prevention of sludge formation
- Excellent engine cleanliness
- Excellent protection at high temperatures
- Excellent wear protection
- Good cold start performance

Applications

Mobil Super™ SemiSintetico 10W-40 is formulated to give you confidence that your engine is receiving protection that goes far beyond what conventional oils can provide. ExxonMobil recommends it if you occasionally experience demanding driving conditions:

- Older engine technologies
- Gasoline and diesel engines without diesel particulate filters (DPF)
- Passenger vehicles, SUVs, light trucks and vans
- Highway cruising and city stop-and-go driving
- Normal to occasionally severe operating conditions

Always refer to your owner's manual to check the recommended viscosity grade and specifications for your specific vehicle.

Specifications and Approvals

| This product has the following approvals: |
|---|
| VW 501 01 |
| VW 505 00 |

| This product is recommended for use in applications requiring: |
|--|
| ACEA A3/B3-16 |
| API CF |

| This product meets or exceeds the requirements of: |
|--|
|--|

This product meets or exceeds the requirements of:

API SN

API SN PLUS

API SP

API SQ

Properties and Specifications

| Property | |
|--|------------|
| Grade | SAE 10W-40 |
| Noack Volatility, mass%, ASTM D5800 | 9.1 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 235 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 102.3 |
| Hi-Temp Hi-Shear Viscosity @ 150 C 1x10 ⁽⁶⁾ sec ⁽⁻¹⁾ , mPa.s, ASTM D4683 | 3.8 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 14.7 |
| Density @ 15.6 C, g/ml, ASTM D4052 | 0.87 |
| Viscosity Index, ASTM D2270 | 149 |
| Pour Point, °C, ASTM D97 | -36 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2026

Terpel Comercial del Perú S.R.L.

Av. Jorge Basadre Grohmann 347,

Interior 1005, San Isidro

Lima, Perú

24 Horas emergencia en salud

LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.



© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved