



MOBIL SUPER 3000 FORMULA F 0W-30

Mobil Passenger Vehicle Lube , Poland

Fully synthetic motor oil

Product Description

Mobil Super 3000 Formula F 0W-30 is a full synthetic motor oil developed to meet the Ford requirement "WSS-M2C950-A". It is designed to help provide long engine life and outstanding protection for diesel engines in a wide range of recently produced passenger vehicle and Light Commercial Vehicle models of Ford.

Features and Benefits

Mobil Super 3000 Formula F 0W-30 meets the technical requirements according to Ford's standard WSS-M2C950-A, based on the OEM engine tests. The usage of this product is meant to provide the following benefits:

- Increased fuel economy¹
 - Extended life of diesel particulate filter²
 - Enhanced lower temperature properties³
1. based on 950-A 0W-30 spec compared to the 913-D 5W-30 oil
 2. based on ACEA C2 requirements
 3. based on 0W-30 spec compared to 5W-30 oil

Applications

Mobil Super 3000 Formula F 0W-30 meets the Ford requirement "WSS-M2C950-A", and can be used for diesel engines in a wide range of recently produced passenger vehicle and Light Commercial Vehicle models of Ford.

Owner's manual should be consulted for recommended viscosity grades and specification.

Specifications and Approvals

| |
|--|
| MOBIL SUPER 3000 FORMULA F 0W-30 meets or exceeds the requirements of the following industry specification: |
| ACEA A5/B5 |

| |
|--|
| This product has the following approvals: |
| VW VWC 53035 |
| STJLR.03.5007 |

| |
|---|
| This product meets or exceeds the requirements of: |
| FORD WSS-M2C950-A |
| ACEA C2 |

Properties and Specifications

| | |
|-----------------|-----------|
| Property | |
| Grade | SAE 0W-30 |

| Property | |
|---|-------|
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 9.6 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 44.7 |
| Viscosity Index, ASTM D2270 | 204 |
| Density @ 15.6 C, g/ml, ASTM D4052 | 0.842 |
| Pour Point, °C, ASTM D97 | -42 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 232 |
| Ash, Sulfated, mass%, ASTM D874 | 0.77 |
| Total Base Number, mgKOH/g, ASTM D2896 | 8 |
| Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684 | 20613 |
| Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683 | 2.96 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2025

ExxonMobil Lubricants & Specialties Europe, division of ExxonMobil Petroleum & Chemicals BV.

This information relates only to products supplied in Europe (including Turkey) and the Former Soviet Union.

ExxonMobil Poland sp. z o.o.

Rondo ONZ 1, 12th Floor

00-124 Warsaw, Poland

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.pl/pl-pl/contact-us>

Tel +48 22 556 29 00

Fax +48 22 620 16 61

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved