



MOBIL DELVAC LEGEND™ 1300 SERIES

Mobil Commercial Vehicle Lube , Qatar

Monograde diesel engine oil

Product Description

Mobil Delvac Legend 1300 Series are excellent monograde diesel engine oils formulated from advanced technology base oils and a balanced additive system. They are specifically engineered for performance in intercooled, turbo-charged engines operating under severe on and off-highway conditions. Mobil Delvac Legend 1300 Series are used in a wide range of applications where a monograde lubricant is recommended. Trucking, mining, quarrying, construction, and agricultural businesses use these products successfully.

Features and Benefits

The features and benefits of Mobil Delvac Legend 1300 series include:

| Features | Advantages and Potential Benefits |
|--|---|
| Excellent protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion | Prolonged engine life, Less wear and Excellent protection against ring sticking |
| Extended TBN reserve | Long-term deposit/wear control and Controls formation of acids when using higher sulfur fuels |

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment
- Light, Medium and heavy duty trucking
- Construction, mining, quarrying, and agriculture applications

Specifications and Approvals

| This product is recommended for use in applications requiring: | MOBIL DELVAC LEGEND 1330 | MOBIL DELVAC LEGEND 1340 | MOBIL DELVAC LEGEND 1350 |
|--|--------------------------|--------------------------|--------------------------|
| Allison C-4 | X | | |
| API CF | X | X | X |
| API SF | X | X | X |

Properties and Specifications

| Property | MOBIL DELVAC LEGEND 1330 | MOBIL DELVAC LEGEND 1340 | MOBIL DELVAC LEGEND 1350 |
|----------|--------------------------|--------------------------|--------------------------|
| Grade | SAE 30 | SAE 40 | SAE 50 |

| Property | MOBIL DELVAC LEGEND 1330 | MOBIL DELVAC LEGEND 1340 | MOBIL DELVAC LEGEND 1350 |
|---|--------------------------|--------------------------|--------------------------|
| Ash, Sulfated, mass%, ASTM D874 | 1.1 | 1.1 | 1.1 |
| Density @ 15 C, g/cm3, ASTM D4052 | | 0.81 | |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 235 | | 250 |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 11.6 | 11.6 | 19.5 |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445 | 101 | 101 | 222 |
| Pour Point, °C, ASTM D97 | -27 | -27 | -15 |
| Total Base Number, mgKOH/g, ASTM D2896 | 10 | 10 | 10 |
| Viscosity Index, ASTM D2270 | 99 | 99 | 99 |

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2025

ExxonMobil

Exxon Mobil 

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved