Mobil

Mobil Super™ 3000 Formula V 5W-30

Mobil Passenger Vehicle Lube , Russia

Fully Synthetic Engine Oil

Product Description

Mobil Super™ 3000 engine oil series are synthetic and engineered to deliver outstanding protection.

Mobil Super™ 3000 Formula V 5W-30 is a high performance, low ash engine oil designed to meet the demanding requirements of extended service life whilst still contributing to superior engine cleanliness. Mobil Super 3000 Formula V 5W-30 delivers excellent high and low temperature performance, provides wear-protection and improved engine cleanliness.

This product is recommended for use in Volkswagen vehicles and a wide range of European cars and light-duty commercial vehicles such as BMW, Mercedes with oil specifications built on the ACEA C3 industry baseline.

Features and Benefits

Mobil Super 3000 Formula V 5W-30 delivers excellent high and low temperature wear-protection and improved engine cleanliness.

Key features and benefits:
- Extended service interval as per VW, MB, BMW requirements
- Compatibility with Particulate Filters and Catalytic Convertors
- Delivers excellent high and low temperature wear-protection
- Improved engine internal cleanliness to maintain engine efficiency over life of vehicle
- Fast oil circulation and protection

Applications

Mobil Super 3000 Formula V 5W-30 has been designed to meet the requirements of modern (Euro 6 or prior) turbo injection diesel and gasoline engines equipped with particle filters or catalitic converters. The oil is also recommended for many BMW and MB passenger vehicles.

- Volkswagen passenger cars and light commercial vehicles or vans (it meets the needs of the latest engine requirements of the VW group where extended drain is required). This motor oil is also recommended for many BMW and MB vehicles.
- Passenger cars and light commercial vehicles or vans requiring ACEA C3 for compatibility with GPF or DPF.
- Gasoline and Diesel with Diesel Particulate Filters (DPF) & Catalytic Convertors.
- Normal to occasionally severe operating conditions (including city driving conditions).

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:
BMW Longlife 04
Porsche C30
VW 504 00
VW 507 00

This product meets or exceeds the requirements of:
API SN
API SN PLUS
API SP

This product meets or exceeds the requirements of:
API SQ
ACEA C3

Properties and Specifications

Property	
Grade	SAE 5W-30
Viscosity Index, ASTM D2270	170
Pour Point, °C, ASTM D97	-42
Flash Point, Cleveland Open Cup, °C, ASTM D92	221
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	69
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	12
Density @ 15.6 C, g/ml, ASTM D4052	0.852

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2026

Mobil Oil Lubricants LLC : 123242, Moscow, Novinsky boulevard, 31, Russia

+ 7 (095) 232 22 23

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: https://www.mobil.ru/ru-ru/contact-us-technical

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved