

**Mobil™ FORMULA X2 5W-40**

Mobil Passenger Vehicle Lube , Taiwan

Full Synthetic Engine Oil

**Product Description**

Mobil™ FORMULA X2 5W-40 is full synthetic engine oil with high quality, designed to offer excellent protection to engines.

**Features and Benefits**

- Helps reduce engine wear and corrosion and excellent anti-wear protection
- Helps keep engine clean
- Outstanding protection under both high and low temperature

**Applications**

Mobil™ FORMULA X2 5W-40 is full synthetic engine oil with high quality, designed to offer excellent protection to engines.

**Specifications and Approvals****This product has the following approvals:**

MB-Approval 229.3

Porsche A40

RENAULT RN0700

RENAULT RN0710

VW 502 00

VW 505 00

**This product is recommended for use in applications requiring:**

API CF

**This product meets or exceeds the requirements of:**

API SN

ACEA A3/B3

ACEA A3/B4

**Properties and Specifications**

Property	
Grade	SAE 5W-40
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	13.8
Pour Point, °C, ASTM D97	-42
Hi-Temp Hi-Shear Viscosity @ 150 C, mPa.s, ASTM D4683	3.7
Density @ 15 C, g/ml, ASTM D4052	0.854
Total Base Number, mgKOH/g, ASTM D2896	10.1
Ash, Sulfated, mass%, ASTM D874	1.1
Flash Point, Cleveland Open Cup, °C, ASTM D92	232
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	83
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	28300

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2020

ExxonMobil international Holding Inc. Taiwan Branch  
6F, No 2, Section 1, Tun Hua South Road  
Taipei Taiwan

+886 2 2734 6888

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved