



Mobil Delvac Modern™ 15W-40 CNG/LNG

Mobil Commercial Vehicle Lube , United States

Premium Synthetic Blend

Product Description

Mobil Delvac™ Modern CNG/LNG engine oil provides excellent performance in the challenging operating environments presented by Compressed Natural Gas (CNG) and Liquefied Natural Gas (LNG), and offers extended drain interval capability.

It is a high-performance, heavy-duty engine oil formulated for diesel engines and spark-ignited, CNG- and LNG-fueled truck and bus engines.

The product has approvals for Cummins CES 20092 and API CK-4 specifications.

Features and Benefits

Features	Advantages and Potential Benefits
Thermal Stability and Oxidation/Nitration Control	Extended Drain Interval Capability
Advanced Wear Protection	Helps Towards Long Engine Life
Effective Detergency/Dispersancy	Engine Cleanliness
Optimized Ash Level	Helps Protect Against Excessive Valve Recession and Spark Plug Fouling
Shear Stability	Engine Durability

Applications

- Spark ignited CNG/LNG fueled stoichiometric and lean-burn engines
- Heavy duty diesel engine requiring API CK-4 specification
- Compatible with Exhaust Gas Recirculation (EGR) Systems, Three Way Catalysts, and other emissions reduction systems

Specifications and Approvals

This product has the following approvals:
Cummins CES 20092

This product meets or exceeds the requirements of:
API CK-4

Properties and Specifications

Property	
Grade	SAE 15W-40
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	15
Pour Point, °C, ASTM D97	-33
Flash Point, Cleveland Open Cup, °C, ASTM D92	223
Density @ 15.6 C, g/ml, ASTM D4052	0.872
Total Base Number, mgKOH/g, ASTM D2896	10
Ash, Sulfated, mass%, ASTM D874	0.9

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2024

Exxon Mobil Corporation


22777 Springwoods Village Parkway
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved