



## MOBIL 1™ EXTENDED PERFORMANCE HIGH MILEAGE

Mobil Passenger Vehicle Lube , United States

Advanced Full Synthetic Motor Oil

### Product Description

Mobil 1 Extended Performance High Mileage motor oil utilizes our signature Triple Action Formula to deliver outstanding engine performance, protection, and cleanliness to vehicles of all ages. Specialty components in synthetic oil extend engine life by reducing deposits and sludge buildup—keeping critical engine parts clean and protected for up to 25,000 miles between oil changes.\* Mobil 1 Extended Performance High Mileage motor oil meets ILSAC GF-7 standards, offering superior oxidation control, enhanced protection against pre-ignition and timing chain wear, and excellent cold-start and low-temperature performance. Mobil 1 is the #1 selling motor oil in America at retail,\*\* trusted and recommended by car builders and experienced mechanics, and is the Official Motor Oil of NASCAR®.

### Features and Benefits

- High Mileage for engines 75,000+ miles
- Exceptional engine performance
- Protects for 25,000 miles – guaranteed\*
- Cleans your engine in 1 oil change
- Improves gas mileage\*\*\*
- Keeps your engine running like new

\*Protects for 25,000 miles or 1 year, whichever comes first

\*\*Source: Circana / Retail Tracking Service/ Dollar Sales/ 52 weeks ending February 1, 2025

\*\*\*vs GF-7 fuel economy requirement

### Applications

- Mobil 1 Extended Performance High Mileage motor oils are designed for engines with over 75,000 miles and are recommended by ExxonMobil for all types of modern gasoline-powered vehicles, including high-performance turbocharged, supercharged, multi-valve fuel injected engines found in passenger cars, SUVs, light vans and trucks.
- Mobil 1 Extended Performance High Mileage is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.
- If your vehicle is covered by a warranty, follow the vehicle's oil life sensor or the oil change interval recommended in your owner's manual. Proper maintenance practices, including frequently checking the oil level to ensure that the appropriate amount of oil is present, are required to ensure effective performance.
- Always check your owner's manual for the manufacturer's recommended oil viscosity grade, API service classification and any builder approval.

### Specifications and Approvals

This product is recommended for use in applications requiring:	0W-20	5W-20	5W-30	10W-30
Chrysler MS-6395	X	X	X	X
FORD WSS-M2C945-B1		X		
Ford WSS-M2C946-A			X	
Ford WSS-M2C946-B1			X	
Ford WSS-M2C947-A	X			
Ford WSS-M2C947-B1	X			
FORD WSS-M2C960-A1		X		
GM 4718M				X
GM 6094M	X	X		X

This product meets or exceeds the requirements of:	0W-20	5W-20	5W-30	10W-30
API SJ		X		
API SL	X	X	X	X
API SM	X	X	X	
API SN	X	X	X	X
API SN PLUS	X	X	X	X
API SN PLUS RESOURCE CONSERVING	X	X	X	X
API SN Resource Conserving	X	X	X	
API SP	X	X	X	X
API SP Resource Conserving	X	X	X	X
API SQ	X	X	X	X
API SQ Resource Conserving	X	X	X	X
ILSAC GF-7A	X	X	X	X
FORD WSS-M2C970-A1		X		
FORD WSS-M2C972-A1	X			

## Properties and Specifications

Property	0W-20	5W-20	5W-30	10W-30
Grade	SAE 0W-20	SAE 5W-20	SAE 5W-30	SAE 10W-30
Density @ 15.6 C, g/ml, ASTM D4052	0.8468	0.8488	0.8475	0.8549
Flash Point, Cleveland Open Cup, °C, ASTM D92	225	242	230	252
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	8.7	8.83	10.37	11.01
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	45.64	48.29	58.65	69.4
Pour Point, °C, ASTM D97	-51	-36	-42	-39

## Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2026

### Exxon Mobil Corporation

22777 Springwoods Village Parkway

Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

The ExxonMobil logo, featuring the word "ExxonMobil" in a stylized, bold, sans-serif font.Three logos are displayed horizontally: the word "Exxon" in a bold, sans-serif font, the word "Mobil" in a bold, sans-serif font, and the Esso logo, which consists of the word "Esso" inside a circular border.

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved