Mobil

Mobil Super™ Synthetic Euro 5W-40

Mobil Passenger Vehicle Lube , United States

Advanced Full Synthetic Engine Oil

Product Description

Mobil Super™ Synthetic Euro 5W-40 is a full synthetic high-performance motor oil, which provides excellent high temperature protection. Mobil Super Synthetic is designed to help provide long engine life and outstanding protection in vehicles of all ages, outperforming our conventional-synthetic blended products. This oil provides outstanding protection against sludge, engine rust and corrosion under severe and low-temperature operating conditions and provide optimum viscosity and fluidity across a broad range of temperatures.

We stand behind our products. Read our Mobil Super limited warranty.

For our ultimate in performance and protection consider our Mobil 1™ motor oils, a family of advanced full synthetic motor oil.

Features and Benefits

•Helps extend engine life

•Outstanding wear protection for vehicles of all ages

•Excellent high temperature protection to help keep engines cool

•Permits extended operation at elevated temperatures (up to 400º F) without oxidative oil thickening and oil breakdown

•Helps control oil consumption and loss

•Allows easy starting and rapid oil circulation during cold starts to protect critical engine parts

•Specifically formulated to support European designed engines

•Protection beyond our conventional-synthetic blended products

•Guaranteed protection with Mobil Super Limited Warranty*

•Meets or exceeds the latest applicable OEM and industry specifications*

*See “Specifications and Approvals" table for more information

Applications

Mobil Super Synthetic Euro 5W-40 are recommended for vehicles required an European spec product. Before using Mobil Super Synthetic motor oils, consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and API Service Classification.

Specifications and Approvals

This product has the following approvals:
BMW Longlife 01
MB-Approval 229.3
MB-Approval 229.5
RENAULT RN0700
RENAULT RN0710

This product has the following approvals:
VW 502 00
VW 505 00
Porsche A40

This product is recommended for use in applications requiring:
API CF
FIAT 9.55535-G2

This product meets or exceeds the requirements of:
API SL
API SM
API SN
API SN PLUS
API SP
ACEA A3/B4

Properties and Specifications

Property	
Grade	SAE 5W-40
Pour Point, °C, ASTM D97	-39
Flash Point, Cleveland Open Cup, °C, ASTM D92	236
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	78.0
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	13.1
Density @ 15.6 C, g/ml, ASTM D4052	0.8469

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2026

Exxon Mobil Corporation

22777 Springwoods Village Parkway
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved