



MOBIL SUPER MOTO GREASE

Mobil Passenger Vehicle Lube , Uruguay

High-performance multipurpose grease for motorcycles

Product Description

MOBIL SUPER MOTO GREASE™ is a lithium complex, mineral oil-based multipurpose grease specially formulated for motorcycle applications. It provides excellent performance over a wide temperature range and offers moderate load carrying capability, extreme pressure properties, water resistance, oxidation stability, and rust and corrosion protection. It is NLGI GC-LB qualified, making it suitable for critical motorcycle components such as wheel bearings and chassis lubrication points.

Features and Benefits

MOBIL SUPER MOTO GREASE™ offers the following features and potential benefits:

- Excellent resistance to high-temperature degradation for long service life, helping to extend grease lubrication intervals.
- Enhanced extreme-pressure and anti-wear properties help protect moving surfaces from wear, leading to extended component life.
- Outstanding high- and low-temperature performance helps minimize cold-weather dispensing problems.
- Good water-resistance properties for reliable grease performance in wet or hostile environments.

Applications

MOBIL SUPER MOTO GREASE™ is recommended by ExxonMobil for motorcycle applications, including:

- Wheel bearings
- Steering head bearings
- Swingarm pivots
- Chassis lubrication points
- Other motorcycle components requiring an NLGI GC-LB qualified grease

Properties and Specifications

Property	
Grade	NLGI 2
Color, Visual	Green
Base Oil Viscosity of Greases @ 40 C, mm ² /s, AMS 1697	115
Penetration, 60X, 0.1 mm, ASTM D217	280
Corrosion Preventive Properties, Rating, ASTM D1743	Pass
Dropping Point, °C, ASTM D2265	260

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2026

DISA Montevideo S.A. - San Fructuoso, 927, Montevideo - Centro Técnico (598) 22009920 interno 55175, en caso de derrames (598) 22007185.

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved