



Mobil Super™ 3000 x1 5W-40

Mobil Passenger Vehicle Lube , Uruguay

Premium Quality Multigrade Semi Synthetic

Product Description

Mobil Super™ 3000 X1 5W-40 is a full synthetic motor oil that provides long engine life for many types & ages of vehicles with enhanced protection over a wide temperature range.

Features and Benefits

Mobil Super™ 3000 products are industry proven so you can trust you will get the performance you want from your vehicle.

Mobil Super™ 3000 X1 5W-40 provides:

- Enhanced high temperature protection
- Enhanced cold start-up performance
- Enhanced engine cleanliness and sludge prevention
- Enhanced wear protection

Applications

Mobil Super™ 3000 products are formulated to give you confidence of protection beyond that of conventional or semi-synthetic oils.

ExxonMobil recommends Mobil Super™ 3000 X1 5W-40 if you regularly experience demanding conditions where it can help combat the damage caused by frequent high engine stress:

- Many engine technologies
- Gasoline and Diesel without Diesel Particulate Filters (DPF)
- Passenger cars, SUV's, light trucks and vans
- Highway cruising and stop and go city driving
- High Performance Engines
- Normal to frequently severe operating conditions
- Turbo-Chargers and Direct Injection engines

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:

MB 229.3

Porsche A40

PSA B71 2296

This product has the following approvals:

RENAULT RN0700

RENAULT RN0710

VW 502 00

VW 505 00

This product is recommended for use in applications requiring:

ACEA A3/B3-16

API CF

FIAT 9.55535-G2

GM-LL-B-025

This product meets or exceeds the requirements of:

API SL

API SM

API SN

API SN PLUS

API SP

ACEA A3/B4

Fiat 9.55535-M2

Properties and Specifications

| Property | |
|--|-----------|
| Grade | SAE 5W-40 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 236 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 78 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 13.1 |
| Density @ 15.6 C, g/ml, ASTM D4052 | 0.85 |
| Viscosity Index, ASTM D2270 | 169 |
| Pour Point, °C, ASTM D97 | -39 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2025

DISA Montevideo S.A. - San Fructuoso, 927, Montevideo - Centro Técnico (598) 22009920 interno 55175, en caso de derrames (598) 22007185.

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved