MOBIL DELVAC™ MODERN OE 10W-30 FULL PROTECTION

Mobil Commercial Vehicle Lube , Japan

合成技術

製品の概要

Mobil Delvac Modern OE 10W-30 Full Protectionは、合成技術を採用した超高性能ディーゼルエンジンオイルです。ディーゼル微粒子捕集フィルター(DPF)装着車を含む、最新の高出力・低排出ガスエンジンで優れた性能を発揮し、オンハイウェイおよびオフハイウェイ用途でエンジン寿命の延長に貢献します。

製品の特長と利益

Mobil Delvac Modern OE 10W-30 Full Protectionは、最適化されたベースオイルと添加剤技術により、酸化安定性、すす処理性、摩耗抑制の強固な基盤を提供し、エンジンの長寿命化とオイル交換周期の延長をサポートします。

特長	利点および期待される効果
すすによる粘度上昇の抑制性能を強化	エンジン効率の維持、エンジン寿命・オイル寿命の延長に貢献
優れた熱安定性と酸化安定性	低温環境でのスラッジ蓄積と高温環境でのデポジットを低減
TBN(全塩基価)保持性能	腐食防止性能の向上とオイル交換周期の延長に貢献
粘度グレードを維持するせん断安定性	高温での使用という過酷な状況下においても粘度を維持し、優れた耐摩耗性と長いエンジ ン寿命を実現
腐食摩耗および研磨摩耗に対する優れた耐性	重要な摩耗面の長寿命化
構成部品との適合性	ガスケット、シール、後処理装置(DPF)の長寿命化

用途

ExxonMobilによる推奨用途:

• Euro V/VIおよびChina V/VI(1)に適合する最新の低排出ガス車を含む大型ディーゼルエンジン
• オンハイウェイ用途の小型・大型トラック輸送
• 建設、鉱業、採石、農業などのオフハイウェイ用途

(1) 詳細な潤滑油要件および適用については、車両のサービスマニュアルを参照してください。

規格および承認

この製品は次の承認を得ています:
CUMMINS CES 20086
CUMMINS CES 20100

この製品は次の承認を得ています:
API CK-4

製品の特性と仕様

代表性状	
グレード	SAE 10W-30

代表性状	
密度@15.6℃、g/mL、ASTM D4052	0.8691
動粘度@100℃、mm^2/s、ASTM D445	11.93
動粘度@40℃、mm^2/s、ASTM D445	80.78
引火点（クリーブランド開放式試験）、℃、ASTM D92	237
粘度指数、ASTM D2270	142
流動点、℃、ASTM D97	-39
全塩基価、mgKOH/g、ASTM D2896 9	9.3
硫酸灰分、質量%、ASTM D874	0.9

健康と安全

本製品の健康と安全に関する推奨事項は、物質安全データシート（MSDS）（http://www.msds.exxonmobil.com/psims/psims.aspx）に記載されています。
本書で使用されているすべての商標は、その他の記載がない限り、Exxon Mobil Corporationまたは同社の子会社の商標または登録商標です。

06-2026

ExxonMobil Japan Godo Kaisha

Shinagawa Grand Central Tower

2-16-4, Konan, Minato-Ku,

Tokyo, 108-8218,

Japan

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved