Mobil Super 2T - 美孚Super 2T

Mobil Passenger Vehicle Lube , Hong Kong

高性能二行程引擎潤滑油

產品簡介

美孚Super 2T是高性能的二行程引擎潤滑油，供摩托車、雪地摩托車及潤滑油/燃油比低的鍊鋸採用。美孚Super 2T預先調稀，以確保加入燃油時能夠快速混合。

特性與效益

美孚Super 2T選用高品質礦物油，加以強大的添加劑配方調製。引擎整體的清淨與操作性能良好。主要特性與效益如下：

特性	優點及潛在效益
抗磨損性質良好	有助於延長引擎壽命
溫度與氧化穩定性；沉澱物控制良好	引擎較乾淨，火星塞壽命延長，極度活塞環粘滯及活塞卡緊現象，且能防止預先點火毛病
抗蝕性良好	有助於延長引擎壽命
減少預先點火毛病	改進燃油效率、延長活塞壽命

應用範圍

美孚Super 2T專為潤滑API TC及JASO FB性能等級的二行程引擎研製。

規格與認可

產品符合或超越以下要求：
API TC
JASO FB
ISO-L-EGB

典型特性

美孚Super 2T	
Viscosity粘度等級，ASTM D 445	
cSt @ 40°C	63
cSt @ 100°C	8.7
Viscosity Index粘度指數，ASTM D 2270	110
Sulfated Ash硫酸鹽灰分，wt%, ASTM D 874	0.05
Pour Point傾點，°C, ASTM D 97	-12

美孚Super 2T	
Flash Point閃點, °C, ASTM D 92	132
Density密度@ 15°C kg/l, ASTM D 4052	0.878

健康與安全

如需有關此產品的健康與安全建議，請參閱材料安全資料表 (MSDS)，其網址為：http://www.msds.exxonmobil.com/psims/psims.aspx

除非另有提及，否則此處使用的所有商標皆為 Exxon Mobil Corporation 或其子公司的商標或註冊商標。

11-2020
ExxonMobil Hong Kong
22nd Floor, Central Plaza,
18 Harbour Road, Wanchai
Hong Kong

+852 3197 8888
http://www.exxonmobil.com

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved