美孚 1™ 5W-30

Mobil Passenger Vehicle Lube , Hong Kong

高階全合成機油

產品說明

美孚 1™ Triple Action Power 先進的全合成機油提供優異傑出的引擎效能、保護以及潔淨。

特色與效益

這對您的引擎來說為何重要:

• 效能:減少日常磨損和嚴苛條件下的壓力，進而延長引擎使用壽命。

• 保護:提供極端溫度防護以免發生故障。

• 潔淨:預防汙染物和油泥累積，使引擎更乾淨。

美孚 1™ Triple Action Power 具備各種特性:

• 效能:讓引擎運轉如新。

• 保護:提供高達 10* 倍的高溫保護能力。

• 潔淨:透過活性清潔劑對抗油泥

美孚 1™ 5W-30 經過精心設計，能提升油電混合引擎的性能與壽命，提供:

• 在水分與燃油汙染下，具備卓越的水分處理能力 **

• 3 倍更佳的乳化穩定性，以抵禦極端條件 ***

• 在 10% 水分汙染下，仍具備卓越的抗腐蝕與防鏽保護 ****

* 基於 Sequence IIIH 測試，與業界標準限值相比
** 基於可濾性測試
*** 基於業界標準的乳化保持測試
**** 基於在更嚴苛測試條件下進行的銅片腐蝕與防鏽測試

應用

美孚 1™ Triple Action Power 適合用於汽油車、柴油車以及混合動力車輛。

關於每一種車的滑油黏度級別和規格的建議，請務必參閱您的用戶手冊。

規範與認證

建議將此產品用於需符合以下規範的應用情境:
Ford WSS-M2C929-A
Ford WSS-M2C946-A
Ford WSS-M2C946-B1
FORD WSS-M2C961-A1

此產品符合或超越以下標準:
API SP Resource Conserving
API SP

此產品符合或超越以下標準:
API SN PLUS
API SN
API SN PLUS RESOURCE CONSERVING
API SQ
API SQ Resource Conserving
ILSAC GF-7A
ACEA A5/B5
ACEA C2
FORD WSS-M2C971-A1

特性與規格

特性	
級數	SAE 5W-30
總鹼值, mg KOH/g, ASTM D 2896	8.3
硫酸灰分，mass%，ASTM D874	0.75
黏度 @ 40 C, mm2/s, ASTM D445	58
HTHS黏度 @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	2.9
黏度 @ 100 C, mm2/s, ASTM D445	9.9
微型旋轉黏度計，-35ºC 條件下的表觀黏度，mPa.s，ASTM D4684	17800
流動點, ºC, ASTM D97	-45
閃火點，Cleveland Open Cup, °C, ASTM D92	239
15.6ºC 下的密度，g/ml，ASTM D4052	0.85
黏度指數, ASTM D 2270	158

健康與安全

本產品健康及安全建議需遵循物質安全資料表（MSDS）提供的指引。有關物料安全資料表可向當地經銷部門或上網獲取
(http://www.msds.exxonmobil.com/psims/psims.aspx)
除非另有說明，否則此處使用的所有商標均為埃克森美孚公司或其子公司的商標或註冊商標。

08-2026
ExxonMobil Hong Kong
22nd Floor, Central Plaza,
18 Harbour Road, Wanchai
Hong Kong

+852 3197 8888

http://www.exxonmobil.com

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved